



PRODUCT DATA SHEET

THE SMART CHOICE

Timber Glow Non slip Decking

Product Ref DCS42
Page 1
First Issue 25 Nov 2005
This Issue 21 Feb 2006

Description

Timber Glow Non slip Decking is a transparent water based coating, based on pure polyurethane resins. It is formulated with granular wax additives to give a textured anti slip coating finish. The product incorporates powerful transparent U.V. inhibiting pigmentation.

Purpose

Timber Glow Non slip Decking is highly water resistant, and may be used with confidence in the proximity of swimming pools and wet areas.

Pigmentation shading enhances the appearance of the finished coating and if used on timber preserves it from UV degradation.

The product is equally useful on concrete paving e.g. footpaths etc. It is essential however that concrete is perfectly clean and generally concrete should be acid etched, flushed with water to neutralise the acid before coating commences.

Surface Preparation

Surfaces that are coated with the product must be thoroughly clean and surface dry before any application of product. A test patch should be done on any previous coating to ensure a good bond is achieved with Timber Glow Non slip Decking; any stains, stencils or other marks should be removed as these would otherwise be "locked in" under the transparent coating finish.

Nail holes and imperfections should be filled with exterior grade filler shaded to the appropriate colour, and allowed to dry, then sanded flush prior to the first coating application.

Timber which has been previously oiled with linseed should either be allowed to age prior coating, or thoroughly washed with organic solvent to ensure proper bonding

Application

The product is supplied as a 2 pack mix, (A) wet, (B) dry. A small amount of the (A) should be thinned with approx. 10% water and used alone as a primer for the work.

Component (B) may then be mixed thoroughly into the remainder of (A) and the mix used to finish the job in two coats, after the primer is dry, also ensuring that each coat is thoroughly dry before the next successive coat.

An alternative application method is to apply part (A) alone to small areas and broadcast the part (B) immediately and uniformly over the wet surface. When completely dry and firm, a further coat of part (A) should be spread over the dry surface. Using this method, no more than 1 sq. m. should be spread before broadcasting Part (B).

Application (2)

Apply generously with good quality paint brush or roller.

Good painting practice recommends that when the product is applied by roller onto large areas, it should be "laid off" with a good quality brush, to dispel any foaming, un-evenness or drips and runs that may be formed by the roller

The product dries quite quickly to its' final film and "laying off" should follow the roller directly.

Coverage

The following can be considered as guides:-

Primer Thin Part A 10%

8 - 20m²/L depending on porosity of surface

Method 1 Top coat 2 coats

10 - 14m²/L per coat

Method 2

Top coat 1 14 - 18 m²/L for coat 1, then broadcast Part (B)

Top coat 2 8 -12 m²/L for coat **after coat 1 is thoroughly dry**

Drying Time

Touch dry within half hour, recoat no less than two hours depending on temperature and other weather conditions.

Cleanup

Clean all equipment with water immediately after use to prevent solidification of material particularly in application equipment.

Packaging

Timber Glow Non slip Decking is available in the following sizes: 10, 4, 1, and 0.5 Litre

Caution

If using technique No 2 for applying, you must ensure the Part (B) is broadcast onto the surface of WET part A

Disclaimer

All Hulett's Paints products are manufactured from raw materials of the highest quality available. As we have no control over the conditions under which our products are used, buyers are advised that no responsibility can be taken for any failure of finished work which is attributable to incorrect transport, storage, handling or application of the product

Hulett's Paints
PO Box 1500
Wangara
WA 6947
www.sportcoat.com.au

TEL (08) 9409 9948
info@timberglow.com
www.timberglow.com

Hulett's Paints
43 Baretta Road
Wangara
WA 6065
www.timberglow.com